Product Model: CZ-10T


Thank you for choosing Airdog car air purifier CZ-10T. In order to have a better user experience, please carefully read through the user guide before

For Customer Support, please contact support@siliconvalleyairexperts.com



Product Structure





- 1. Air Inlet
- 2. Air Outlet
- 3. Sensor Hole (optional)
- 4. Indicator Light
- Power/ Wind Speed Adjustment
- 6. Supply Hub

- 7. Collecting Plates
- 8. Ionization wire frame
- 9. AUTO/Manual Switch
- 10. Push Button
- 11. Back Shroud

Accessories

Charger cable USB DC boost (optional)




Connect




Connect car air purifier with car charger port

How to use?



ON: A short press (approximately 1 second)
OFF: A long press (approximately 3 seconds)



AUTO Mode

When the toggle switch is set on Auto, the air purifier will automatically turn on when it senses the motion (e.g. car starts driving).

Manual Mode

When the toggle switch is set on Manual, press the "ON" button to turn on the air purifier. Pressing the "ON" button also allows you to cycle through the three-level air flow speed.

Wind Speed Indicator Light

When you press the "Power" button to cycle through different speeds, the wind speed indicator will blink. When it blinks once, then stays on, it is level 1 speed. When it blinks twice, then stays on, it is level 2 speed. When it blinks three times, then stays on, it is level 3 speed.

Cleaning Reminder Light

The unit needs to be cleaned when the light is red.

CAUTION

- 1. For the best purification effect, please create an open area for car air purifier.
- Keep good maintenance of ionization wire frame and collecting plates by following the cleaning structure in User Guide.
- 3. Use neutral detergent for cleaning; DO NOT use alkaline detergent (like laundry power).
- 4. DO make sure that collecting plates fully dry up before putting back.

Cleaning & Maintenance



Lightly push the switch to the right to unlock (as pictured). Disassemble the back shroud and take out the collecting plates, (as pictured)



Once the collecting plates are cleaned and fully dried, please fold and put it back in the case.




Disassemble the back shroud and take out the collecting plates (as pictured)



After step two, use a small-sized tool (such as a key) and press the position which is shown in the pic to unlock the collecting plates.



Fully disassemble the collecting plates and use a wet towel to clean off all collecting plates. If it's hard to clean, you could use some alcohol wipes to do a throughly cleaning.



Take out the ionization wire frame (as pictured). CAUTION: DO NOT touch the wires to avoid any damage.



Airdog

Use the embedded felton cleaning wiper that is on the left side of the frame to move back and forth a few times to clean the wires.

CAUTION: DO NOT put too much force on the wiper to avoid any damage.

Put the clean plates back into the car air purifier and begin the reset process.

How to reset after cleaning?

After cleaning, connect the unit with the car charger. Press and hold the ON button for 3 seconds to put it in Reset Mode. (The air quality indicator light will be WHITE and the wind speed indicator light will be RED. It means you reset successfully.) Disconnect power plug and wait for a few seconds before reconnecting. Turn on the unit again. Reset completed.



- · Possible Cause: Too much dust accumulated on the collecting plates.
- Possible Solution: Clean the Ionization wire and collecting plates.


Q&A 2: No Dust Collection

- · Possible cause: Ionization frame damaged.
- · Solution: Contact our customer support for a replacement.

Q&A 3: Poor Cleaning Results

- · Possible Cause: Dust collection overload on electrodes.
- · Possible Solution: Clean collecting plates by following " Cleaning & Maintenance".





Specification

Model: CZ-10T

Power Input: Car charger

Voltage Input: 12V ...

Power: 6W

PM2.5 Removal Rate: 94.5% / hr*

Size: 206*175*61 (mm)

Wind Speed: 1-stage, 2-stage, 3-stage

All the parameters above execute under National Home Appliance Safety Standard.

*Testing methods: Run CZ-10T car air purifier in a 3 cubic meters with top stage for an hour; At the beginning, the density of particles over 0.3um is 2*10(6) /L; Using standard testing cigarette with the 8mg tar content.



C7-10T**USFR GUIDE**

